

APS-055

FLUSH-MOUNTED 5 VDC / 0.5 A POWER SUPPLY

The **APS–055** switching power supply is designed for powering 5 VDC devices. It can be used as an external power source for SATEL wireless keypads, e.g.:

- INT-KWRL2 (electronics version 3.2 or newer),
- PRF-LCD-A2 (electronics version 2.2 or newer),
- PRF-LCD-WRL (electronics version 2.2 or newer),
- VERSA-KWRL2 (electronics version 2.2 or newer).
- Nominal output voltage (according to IEC 38): 5 VDC.
- Output voltage stabilization.
- Output current: 0.5 A.
- Input interference filter.
- Electronic short-circuit protection of AC mains power supply circuit.
- Electronic short–circuit and overload protection of the power output.
- Mounted in in-wall and on-wall electrical junction boxes with a minimum diameter of 60 mm



TECHNICAL DATA

| Environmental class | II |
|--|-------------------|
| Operating temperature range | -10°C+55°C |
| Weight | 37 g |
| Dimensions | 47 x 47,4 x 22 mm |
| Rated output voltage | 5 V DC |
| Energy efficiency | up to 72% |
| Nominal output voltage (according to IEC 38) | 5 V DC |
| Power supply type (according to EN50131) | В |
| Power supply output current | 500 mA |
| Supply voltage | 195265 V AC |
| Current consumption by power supply circuits | 3 mA |