

XD-2L

MULTIPURPOSE DETECTOR

The XD–2L is a multipurpose wired detector, which can operate with any alarm control panel. The device can work as: magnetic contact, shock detector, shock detector and magnetic contact, and water flood detector.

The detector is available in white (XD–2L), brown (XD–2L BR) and dark grey (XD–2L DG).

- option to select detector type with DIP switches
- · modes of operation:
 - · magnetic contact
 - detection of opening of a door, window, etc.
 - input for connecting an NC-type wired detector (e.g. other magnetic contact)
 - 1 alarm output
 - o shock detector
 - detection of shocks and vibrations accompanying attempts to force a door or window, etc.
 - input for connecting an NC-type wired detector (e.g. other magnetic contact)
 - 1 alarm output
 - $\circ\,$ shock detector and magnetic contact
 - detection of shocks and vibrations accompanying attempts to force a door or window
 - detection of opening of a door, window, etc.
 - input for connecting an NC-type wired detector (e.g. other magnetic contact)
 - 1 or 2 alarm output(s)
 - water flood detector
 - detection of flooding in rooms with plumbing
 - input for connecting external flood probe FPX-1 (white), FPX-1 BR (brown) or FPX-1 DG (dark grey) the probe available separately
 - 1 alarm output
- $\bullet\,$ option to select alarm output type (2EOL/NC or NC)
- option to select EOL resistors for 2EOL configuration
 - $\circ\,$ alarm: 1.1 k Ω / 2.2 k Ω / 4.7 k Ω / 5.6 k Ω / 6.8 k Ω
 - \circ tamper: 1.1 k Ω / 2.2 k Ω / 4.7 k Ω / 5.6 k Ω
- LED indicator
- remote enabling/disabling of the LED indicator
- supply voltage control
- tamper protection against enclosure opening
- 2 magnets included (for surface and flush mounting)

