

AMD-100

WIRELESS MAGNETIC CONTACT

Magnetic contact detectors belong to the essential perimeter security devices. They are used to protect doors, windows, etc. by triggering alarm when they are open. AMD–100 is a wireless model designed for operation as part of the **ABAX** two–way wireless system. The use of two built–in reed switches allows you to choose the method of installation: the magnet interacting with the sensor can be placed either under or at the side of the detector, depending on the needs. The device comes with tamper protection, test mode LED indicator and an additional input for connecting another NC type detector. AMD–100 is compatible with **INTEGRA 128–WRL** control panel, **ACU–120**, **ACU–270** and the older **ACU–100**, **ACU–250** controllers, as well as with **ARU–100** radio signal repeater. It meets the requirements of EN 50131–2–6 for Grade 2.

The AMD–100 detector is available in two color versions: white (AMD-100) and brown (AMD-100) BR).

- two reed contacts for easy installation
- terminals for connecting external detector
- remote configuration
- tamper protection



TECHNICAL DATA

Additional input sensitivity	312 ms
Battery working time (in years)	Estimated 3 years
Enclosure dimensions	24 x 110 x 27 mm
Operating temperature range	-10+55 °C
Standby mode current consumption	50 μA
Max. current consumption	16 mA
Weight	56 g
Maximum humidity	93 ±3%
Operating frequency band	868,0 ÷ 868,6 MHz
Radio communication range (in open area)	up to 500 m m
Battery	CR123A 3V
Environmental class according to EN50130-5	
Complied with standards	EN 50130-4, EN 50130-5, EN 50131-1, EN 50131-2-6, EN 50131-5-3
Security grade according to EN50131-2-6	Grade 2

