

# **MMD-300 BR**

## WIRELESS MAGNETIC CONTACT

Magnetic detector of open doors and windows, representing the "first line of defense". With the **MMD–300**, the alarm system will react to intrusion before the intruder manages to get into the protected area.

#### Features:

- compatible with MICRA alarm module, PERFECTA 16-WRL, PERFECTA 32-WRL, PERFECTA 32-WRL LTE, PERFECTA-IP 32-WRL, PERFECTA-T 32-WRL and PERFECTA 64 M (equipped with PERFECTA-RF module) control panels as well as VERSA-MCU and MTX-300 wireless system controllers,
- radio signals from a detector can be retransmitted by MRU-300
- two optional reed switch sensors to facilitate selection of installation place,
- input for connecting an external sensor to protect two points (e.g. two sashes of one window) with a single device,
- energy management system to enable many years of operation without having to replace the CR123A lithium battery,
- detection of tamper, e.g. opening enclosure, ripping away from mounting surface
- enclosure color: brown

#### Application

Perimeter protection of small–size buildings, such as kiosks, summer houses, boutiques, freestanding garages and workshops

#### Delivery set:

Detector, flush- or surface-mounted magnets, CR123A lithium battery, mounting elements, user manual



### **TECHNICAL DATA**

312 ms
ll ll
24 x 110 x 27 mm
-10+55 °C
80 μA
27 mA
64 g
93 ±3%
433,05 ÷ 434,79 MHz
CR123A 3V
Estimated 3 years