

SP-4004 R

EN50131 GRADE 2 COMPLIANT SIREN WITH OPTICAL SIGNALLING

The **SP-4004** siren distinguishes itself with its technology of protection against harsh environmental conditions. This protection allows it to ensure full compliance with the rigorous requirements of EN50131 for the Grade 2 sounders. Optional backup battery allows to use the SP-4004 in a self contained mode for the installations in places particularly exposed to tampering risk.

- full EN50131 Grade 2 compliance
- acoustic signalling: piezo
- optical signalling: LED
- inner metal shield
- tamper protection against:
 - removal from mounting
 - opening
- optional 6 v 1,2 Ah battery
- built-in level to facilitate aesthetic mounting
- available also in blue (**SP-4004 BL**)



TECHNICAL DATA

Supply voltage	12 V DC
Operating temperature range	-25°C ...+70°C
Standby mode current consumption	40 mA
Weight	960 g
Maximum humidity	93±3%
Dimensions	148 x 254 x 64 mm
Environmental class according to EN50130-5	IV
Sound pressure level at 1m	up to 120 dB
Maximum current consumption (signaling)	260 mA
Maximum current consumption (signaling + battery recharging)	600 mA



The actual appearance of the products may differ from the presented images. Product descriptions are provided in the web service for information purposes only.